

**PRODUCT DATA SHEET****Avery® MPI™ 3020**

issued: 24/04/2006

**Introduction**

Avery Multi Purpose Inkjet vinyl 3020 is a matt white monomeric calendered permanent self adhesive vinyl. It is suitable for use on a variety of super wide format inkjet and airbrush printers using solvent ink.

**Because of the film's excellent permanent adhesive, Avery MPI 3020 is recommended for a wide range of short term promotional applications on flat substrates.**

**Description**

Film : 95 micron matt white monomeric calendered vinyl  
Adhesive : permanent acrylic  
Backingpaper : kraft paper, 140 g/m<sup>2</sup>

**Conversion**

Avery MPI 3020 is a multi-purpose vinyl, developed for use on various super wide format printers using solvent inks.

In Avery Technical Bulletin 5.15, printer compatibility details of Avery MPI media are listed.

To enhance colour and protect images against UV radiation and abrasion, Avery MPI 3020 is recommended to be overlaminated with Avery® DOL 3000 Gloss, Avery® DOL 3100 Matt or Avery® DOL 3200 Lustre. For an overview of recommended combinations of DOL films and media, please refer to "[Technical Bulletin 5.3. Recommended combinations of Avery® Overlaminates and Avery® Digital Print Media](#)".

**Uses**

- Interior & exterior signs.
- Window decoration.
- Temporary promotional and point of sale advertising and all applications to flat or regular surfaces

**Features**

- Excellent printability and handling on selected printers.
- Easy cutting and application.
- Excellent price/performance ratio for outdoor promotional graphics.

[www.averygraphics.com](http://www.averygraphics.com)

Graphics & Reflective Products Division  
Rijndijk 86, P.O. Box 118  
2394 ZG Hazerswoude – The Netherlands  
Tel +31 71 3421500 – Fax +31 71 3421538

Page 1 of 2



## PRODUCT CHARACTERISTICS

### Avery® MPI™ 3020

#### Physical properties

| Features   | Test method <sup>1</sup>     | Results            |
|--|------------------------------|--------------------|
| Caliper, facefilm  | ISO 534                      | 95 micron          |
| Opacity  | ISO 2471                     | 92%                |
| Dimensional stability  | DIN 30646                    | 0,3 mm max.        |
| Adhesion, initial  | FINAT FTM-1, stainless steel | 600 N/m            |
| Adhesion, ultimate   | FINAT FTM-1, stainless steel | 800 N/m            |
| Flammability   |                              | Self extinguishing |
| Shelf life   | Stored at 22° C/50-55 % RH   | 2 years            |
| *Not when applied to: Nitrocellulose paints, ABS, Polystyrene, screenprinting inks (fresh), certain types of PVC |                              |                    |
| Durability, unprinted  | Vertical exposure            | 2 years            |

#### Temperature range

| Features                         | Results         |
|----------------------------------|-----------------|
| Minimum application temperature: | ≥ 0° C          |
| Temperature range:               | - 40 to +100 °C |

#### Important

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use.

All technical data are subject to change. In case of any ambiguities or differences between the English and foreign versions of these Conditions, the English version shall be controlling.

#### Warranty

Avery® branded materials are manufactured under careful quality control and are warranted to be free from defect in material and workmanship. Any material shown to our satisfaction to be defective at the time of sale will be replaced without charge. Our aggregate liability to the purchaser shall in no circumstances exceed the cost of the defective materials supplied. No salesman, representative or agent is authorised to give any guarantee, warranty, or make any representation contrary to the foregoing.

All Avery® branded materials are sold subject to the above conditions, being part of our standard conditions of sale, a copy of which is available on request.

#### 1) Test methods

More information about our test methods can be found on our website.

#### 2) Durability

The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased.



[www.averygraphics.com](http://www.averygraphics.com)

#### Graphics & Reflective Products Division

Rijndijk 86, P.O. Box 118  
2394 ZG Hazerswoude – The Netherlands  
Tel +31 71 3421500 – Fax +31 71 3421538