



POLI-FLEX BLOCKOUT

Product Information

POLI-FLEX BLOCKOUT is a Sublimation-resistant, multi-layer polyurethane film with a high opacity and a pleasantly soft touch. Even high temperatures will not cause any sublimation inks to bleed through the garment.

POLI-FLEX BLOCKOUT is suitable to transfer onto textiles like cotton, mixtures of polyester/cotton and polyester/acrylic. POLI-FLEX BLOCKOUT can be used for lettering on T-shirts, sport & leisure wear, sport bags and promotional articles.

POLI-FLEX BLOCKOUT can be cut with all current plotters. We recommend using a standard 45° knife. After weeding the cut flex film is transferred by heat press. **To avoid a sublimation-migration we recommend that the garment is not pre-heated.** The polyester liner should be removed warm. Afterwards we recommend pressing the material for another 2 sec. with the same parameters. Nylon and textiles with hydrophobic impregnation are not suitable for heat transfer. In this case we recommend using POLI-FLEX NYLON.

The soft, elastic carrier film offers a comfortable textile touch and convinces due to high wearing comfort. POLI-FLEX BLOCKOUT excels due to an excellent opacity. POLI-FLEX BLOCKOUT with a self-adhesive polyester liner enables a reposition. The raw materials are ecologically inert, do not contain PVC, plasticizers or heavy metals (in accordance with Oeko-Tex Standard 100).

Guarantee for a secure and long-lasting bond of POLI-FLEX BLOCKOUT is only given when following the specified temperature and pressure conditions.

We recommend evaluation on test material.

Due to the various influences which occur from production and transfer of plotter letterings, consistency of the carrier materials and also washing and cleaning conditions, product liability of course can only cover the unprocessed

Technical Data

Carrier:	PET-film
Adhesive:	Polyurethane-hotmelt
Thickness [mm]:	0.115 +/- 5 %

Transfer Conditions

Temperature:	155° - 165° C
Pressure:	3.5 bar [medium pressure]
Time:	17 – 20 sec.

Wash Resistance

Wash resistance:	60° C Only colour and mild detergent. Wash textile inside out.
-------------------------	--

Standard Dimensions

500 mm x 25 m
1,000 mm x 25 m
1,524 mm x 25 m

25/09/2008

POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17

53424 Remagen – GERMANY

Phone: +49 (0) 2642 – 9836 0

Fax: +49 (0) 2642 – 9836 37

E-Mail: info@poli-tape.de

Internet: www.poli-tape.de

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.