



## PRODUCT INFORMATION

Mod. R&S. 05/1  
Pag. 1/1  
Last Updating: 10/2008

# COLORPRINT CRYSTAL MATT/GLOSSY

### Description

Transparent Heat seal material, specifically formulated for ink jet solvent and eco solvent based inks – printing and cutting systems or thermoresin. The material is very thin, suitable for light coloured fabrics.

### Basic Information

Due to the many different base materials available on the market, the following heat transfer instructions are given as guideline only:

**Temperature:** 160-165°C

**Time:** 15"

**Pressure:** medium

### Application Instructions

- 1) **Before printing, remove the additional, external protective film (very easy to detach).**
- 2) **Print in reverse**, on the layer previously covered with the protective film and cut the material
- 3) Let the print dry at least 12 hours before rolling, overlaying or heat transferring the material
- 4) Weed the exceeding material
- 5) Heat apply with its own polyester backing
- 6) Remove backing once **cold**

### Suitable for

Cotton, polyester, poly-cotton blends.

Not suitable for treated and dyed garments (sublimation inks)

**Washing:** (wait 24h after the heat transfer)

50°C Max. – wash inside out - do not use bleach or other aggressive chemical agents

**Dry-cleaning :** no

**Tumble drier :** no

*N.B. : all information given in this sheet are based on our experience*

***We recommend to always perform a test before starting standard production***

The product meets the Italian and Ue regulations relating to its proper use.

This document can be subject to variations. Updated versions are available on our website [www.siser.it](http://www.siser.it).

For further information, please contact our Sales Office. Thank you.